



Fabric Specification Sheet

Style:	<u>Primo 4 Projection Screen</u>		
Available Widths:	98" - 120" (249 cm- 305cm) Other widths Available upon request		
Roll Lengths:	50yard standard (45.72 Meters)		
Colors Available:	Blue/White, Logain Grey face side color with Black back side surface.		
Shipping:	Rolls shipped on 3" (7.62 cm) ID paper or steel cores (120" Shipped on steel cores only)		
Construction:	4 ply laminate (69% PVC vinyl and 31% fiberglass) (Each vinyl is equal thickness and weight)		
Surface Texture:	Embossed		
Thread Count:	68 threads per square inch (26 per square centimeter)		
Weight Per Sq. Yard:	17.9 ounces (606 grams/m ²)	(+ or - 2.0) (+ or - 68)	
Thickness:	16.9 mil (.42 millimeters)	(+ or - 2.0) (+ or - .05)	
Tear Strength:	Warp 8.60 Lbs/In	Fill 10.52 Lbs/In	
Breaking Strength:	Warp 339 Lbs/In	Fill 256 Lbs/In	
Opacity: Visual check	Blackout		
Washability:	Material may be dusted with a damp cloth. When scrubbing is necessary, warm water, mild detergents, and gentle rubbing are recommended.		
Gain:	1.0		
Flammability:	Meets or exceeds National Fire Protection Association Standard 701/2010 (Small Scale)		



Revised 2/1/18

MAILING ADDRESS
P.O. Box 1017
Warsaw, IN 46581

STREET ADDRESS
102 Enterprise Drive
Warsaw, IN 46580

PHONE
(574) 269-1280

FAX
(574) 269-7747

E-MAIL
Mail@indianacoatedfabrics.com

WEBSITE
www.indianacoatedfabrics.com