



# Fabric Specification Sheet

**Style:** **3-Ply 14oz Wideshade III**

**Available Widths:** 84", 98", 120"  
(213 cm, 249 cm, 305 cm)  
(Other widths and colors available, MOQ's may apply)

**Roll Lengths:** 28 yards standard (Other lengths available upon request)  
(25.6 m)

**Shipping:** Rolls shipped on 3" (7.62 cm) ID paper core

**Construction:** 3 ply laminate (60% Vinyl and 40% Fiberglass)  
(Each vinyl is equal thickness and weight)

**Surface Texture:** As laminated

**Thread Count:** 68 threads per square inch  
(26 per square cm)

**Weight:** 14.6 oz per square yard (+ / - 2.0)  
(495 grams per square meter) (+ / - 68)

**Thickness:** 14 mil (+ / - 2.0)  
(.36 mm) (+ / - .05)

**Instron Tear Strength:** Warp 6 Lbs/In Fill 10 Lbs/In

**Instron Breaking Strength:** Warp 338 Lbs/In Fill 298 Lbs/In

**Opacity:** Room Darkening  
**Visual check**

**Washability:** Material may be dusted with a damp cloth. When scrubbing is necessary, warm water, mild detergents and gentle rubbing are recommended.

**Flammability:** NFPA Standard 701/2019 Test Method 1 (Small Scale)

**Other Tests Passed:** AATCC 183 – Blocking Ultraviolet  
FTMS 191A-5660 – Colorfastness to Light  
UL GreenGuard Gold Certified



Revised 1/2020

MAILING ADDRESS  
P.O. Box 1017  
Warsaw, IN 46581

STREET ADDRESS  
102 Enterprise Drive  
Warsaw, IN 46580

PHONE  
(574) 269-1280

FAX  
(574) 269-7747

E-MAIL  
Mail@indianacoatedfabrics.com

WEBSITE  
www.indianacoatedfabrics.com