



# Fabric Specification Sheet

**Style:** **4-Ply 17oz Wideshade IV Ultra**

**Available Widths:** 120"  
(305cm)

**Roll Lengths:** 25 yard standard  
(23 m)

**Shipping:** Rolls shipped on 3" (7.62 cm) ID paper core

**Construction:** 4 ply laminate (70% Vinyl and 30% Fiberglass)  
(Each vinyl is equal thickness and weight)

**Surface Texture:** As Laminated – Various embossing patterns available

**Thread Count:** 68 threads per square inch  
(23 per square cm)

**Weight:** 17.9 oz per square yard (+ or - 2.0)  
(606 grams per square meter) (+ or - 68)

**Thickness:** 16.9 mil (+ or - 2.0)  
(.42 mm) (+ or - .05)

**Instron Tear Strength:** Warp 9 Lbs/In Fill 10 Lbs/In

**Instron Breaking Strength:** Warp 339 Lbs/In Fill 256 Lbs/In

**Opacity:** Blackout  
**Visual check**

**Washability:** Material may be dusted with a damp cloth. When scrubbing is necessary, warm water, mild detergents and gentle rubbing are recommended.

**Flammability:** NFPA Standard 701/2019 Edition Test Method 1 & 2

**Other Tests Passed:** ATSM D3335 85a Lead Test  
UL GreenGuard Gold Certified

No.	Description	Ts	Rs	As	Tv	Rv	Av	Tv	O-F	SC (Single Glass)			SC (Insulating Glass)		
										1/8" CI	1/4" CI	1/4" H.A.	1/2" CI	1" CI	1" H.A.
11	White 4 Ply	Tr	79	21	Tr	67	33	Tr	0.2	0.19	0.21	0.25	0.19	0.22	0.2



Revised 1/2020

MAILING ADDRESS  
P.O. Box 1017  
Warsaw, IN 46581

STREET ADDRESS  
102 Enterprise Drive  
Warsaw, IN 46580

PHONE  
(574) 269-1280

FAX  
(574) 269-7747

E-MAIL  
Mail@indianacoatedfabrics.com

WEBSITE  
www.indianacoatedfabrics.com