

the Iconic Blackout Collection

Specifications Fabric Line

Construction	4 ply (PCE Film, Fiberglass)
Thread Count	60 threads per square inch
Available Widths	36", 54", 63", 72", 77" (91 cm, 137 cm, 160 cm, 183 cm, 196 cm)
Roll Lengths	33 yards (33 m) on 3" cores (Other lengths available upon request)
Weight	12 oz per square yard (424 grams per square meter)
Thickness	12.5 mil (.318 mm)
Instron Tear Test Lbs./ft.	Warp: 25.87 Fill: 17.53
Instron Breaking Strength Lbs./In.	Warp: 100 Fill: 77
Opacity	Blackout
Flammability	NFPA 701 Test Method 1 - 2019 Edition Also available as "Ultra" (CAN-ULC-S109)
Care & Handling	May be dusted with damp cloth. Warm water, mild detergent with gentle rubbing when scrubbing is necessary
Testing & Certifications	NFPA Standard 701/2019 Test Method 1 FMVSS & CMVSS 302 California State Fire Marshal Sec. 13115 Registration FA-35801 SW 846-7000B-7420 (Pb) - Lead ASTM D4834-03/CSA-CAN 600.008 Lead ASTM G-21 Resistance to Fungi

the Standard Blackout

Construction	4 ply (PCE Film, Fiberglass)
Thread Count	60 threads per square inch
Available Widths	36", 54", 63", 72", 77" (91 cm, 137 cm, 160 cm, 183 cm, 196 cm)
Roll Lengths	33 yards (33 m) on 3" cores (Other lengths available upon request)
Weight	12 oz per square yard (424 grams per square meter)
Thickness	12.5 mil (.318 mm)
Instron Tear Test Lbs./ft.	Warp: 25.87 Fill: 17.53
Instron Breaking Strength Lbs./In.	Warp: 100 Fill: 77
Opacity	Blackout
Flammability	NFPA 701 Test Method 1 - 2019 Edition Also available as "Ultra" (CAN-ULC-S109)
Care & Handling	May be dusted with damp cloth. Warm water, mild detergent with gentle rubbing when scrubbing is necessary
Testing & Certifications	NFPA Standard 701/2019 Test Method 1 FMVSS & CMVSS 302 California State Fire Marshal Sec. 13115 Registration FA-35801 SW 846-7000B-7420 (Pb) - Lead ASTM D4834-03/CSA-CAN 600.008 Lead ASTM G-21 Resistance to Fungi

the Economy Wide Shade

Construction	4 ply (PCE Film, Fiberglass)
Thread Count	60 threads per square inch
Available Widths	98", 120" (249 cm, 305 cm)
Roll Lengths	25 yards (23 m) on 3" cores (Other lengths available upon request)
Weight	14.5 oz per square yard (492 grams per square meter)
Thickness	15.2 mil (.386 mm)
Instron Tear Test Lbs./ft.	Warp: 40.05 Fill: 21.61
Instron Breaking Strength Lbs./In.	Warp: 293.33 Fill: 304.62
Opacity	Blackout
Flammability	NFPA 701 Test Method 1 - 2019 Edition Also available as "Ultra" (CAN-ULC-S109)
Care & Handling	May be dusted with damp cloth. Warm water, mild detergent with gentle rubbing when scrubbing is necessary
Testing & Certifications	ATCC 6275 Aspergillus Niger/ATC 9645 Trichoderma Virus ASTM E1428-9 Pink Staining AATCC 183 - UV Blocking AATCC 16, Option 3 - 2003 Colorfastness to Light ASHRAE Standard 74-1988 - Fenestration GreenGuard - Gold Certified

the Wide Shade IV

Construction	4 ply (PCE Film, Fiberglass)
Thread Count	68 threads per square inch
Available Widths	98", 120" (249 cm, 305 cm)
Roll Lengths	25 yards (23 m) on 3" cores (Other lengths available upon request)
Weight	17.5 oz per square yard (606 grams per square meter)
Thickness	16.9 mil (.42 mm)
Instron Tear Test Lbs./ft.	Warp: 9 Fill: 10
Instron Breaking Strength Lbs./In.	Warp: 339 Fill: 256
Opacity	Blackout
Flammability	NFPA 701 Test Method 1 - 2019 Edition Also available as "Ultra" (CAN-ULC-S109)
Care & Handling	May be dusted with damp cloth. Warm water, mild detergent with gentle rubbing when scrubbing is necessary
Testing & Certifications	ATCC 6275 Aspergillus Niger/ATC 9645 Trichoderma Virus ASTM E1428-9 Pink Staining AATCC 183 - UV Blocking AATCC 16, Option 3 - 2003 Colorfastness to Light ASHRAE Standard 74-1988 - Fenestration GreenGuard - Gold Certified

Color & Embossing

Color Match	White to Grey Tones										Neutral to Brown Tones																							
	11	12	105	106	92	47	109	109	111	118	142	10	75	37	23	51	57	34	103	104	84	26	9	32	101	100	104	104	33	38	45	36	39	
45" (114 cm)	X	X										X				X	X																	
54" (137 cm)	X	X			X		X					X				X	X								X						X			
63" (160 cm)	X				X		X					X				X									X									
72" & 96" (91 & 183 cm)	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X
77" (196 cm)	X											X					X																	
98" (249 cm)	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X
120" (305 cm)	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X
120" Ultra (305 cm)	X	X			X		X					X																						

Embossing Pattern	the Standard	Wide Shade
	[36", 54", 63", 72", 77"]	[98" & 120"]
Matte	X	X
DeLux	X	X
Moire	X	X
Boucle	X	X
Cloud	X	
Pebble	X	
Windsor	X	
Medina	X	
Leather	X	
Linen Plus	X	
Topaz	X	X
Sofglass	X	

Solar Control (12 oz 4-ply)

Solar Heat Control Properties																
Interior Use at Zero Degree Profile Angle																
No.	Color	T _s	R _s	A _s	T _v	R _v	A _v	T _v	O-F	SC (Single Glass)			SC (Insulating Glass)			
										1.8" CI	1/4" CI	1/4" H.A	1/2" CI	1" CI	1" H.A	
11	White 4 Ply	Tr	77	23	Tr	NA	NA	NA	NA	0.22	NA	NA	0.2	NA		
23	Bone 4 Ply	Tr	69	31	Tr	59	41	Tr	0.2	0.27	0.28	0.29	0.26	0.28	0.23	
47	Grey 4 Ply	Tr	45	55	Tr	Tr	Tr	NA	NA	0.44	0.43	0.37	NA	NA	NA	
49	Dark Grey 4 Ply	Tr	30	70	Tr	28	72	Tr	0.2	0.55	0.53	0.42	0.52	0.49	0.35	
10	Black 4 Ply	Tr	5	95	Tr	Tr	Tr	NA	NA	0.72	0.68	0.5	NA	NA	NA	

Fabrication

Cutting: Cold, Electric Rotary Sheer, Straight Knife, Crush Cut, Ultrasonic | **Welding:** Heat Seal, RF

Application

Roller Shade, Panel Track, Verticals, Banner/Print Media



Ask us about our other fabric lines which include: Cotela-TFR, the Apagón Collection, the Vision Collection, and the Commercial Collection

www.indianacoatedfabrics.com

102 Enterprise Drive - P.O. Box 1017 - Warsaw, IN 46581

info@indianacoatedfabrics.com