



Fabric Specification Sheet

Style:	<u>MW-8</u>	
Available Widths:	72" Other widths available upon request (183 cm)	
Roll Lengths:	100 yards standard (91.44 m)	
Colors Available:	Blue/White, Logain Grey face side color with Black back side surface	
Shipping:	Rolls shipped on 3" (7.67 cm) ID paper cores.	
Construction:	3 ply laminate (65% vinyl and 35% fiberglass) (Each vinyl is equal thickness and weight)	
Surface Texture:	Topaz Embossing Pattern	
Thread Count:	60 threads per square inch (23 per square centimeter)	(+4 / -6)
Weight:	9.7 oz. per square yard (329 grams per square meter)	(+ / - 2.0) (+ / - 68)
Thickness:	9.5 mil (.241 millimeters)	(+ / - 2.0) (+ / - .05)
Instron Tear Test Grams:	Warp 19.16	Filling 18.81
Instron Breaking Strength Lbs./in.:	Warp 127	Filling 113
Opacity: Visual check	Blackout.	
Washability:	Material may be dusted with a damp cloth. When scrubbing is necessary, warm water, mild detergents, and gentle rubbing are recommended.	
Flammability:	Meets or exceeds NFPA Standard 701/1996 (Small Scale) ASTM G21	



Revised 2/1/18

MAILING ADDRESS
P.O. Box 1017
Warsaw, IN 46581

STREET ADDRESS
102 Enterprise Drive
Warsaw, IN 46580

PHONE
(574) 269-1280

FAX
(574) 269-7747

E-MAIL
Mail@indianacoatedfabrics.com

WEBSITE
www.indianacoatedfabrics.com