



Iconic Blackout

By ICF

The Blackout Standard

Style: Standard, Economy WideShade,
WideShade IV



Indiana
Coated
Fabrics

www.indianacoatedfabrics.com

102 Enterprise Drive - P.O. Box 1017 - Warsaw, IN 46581

the Iconic Blackout Collection

Specifications

Fabric Line

Construction

Thread Count

Available Widths

Roll Lengths

Weight

Thickness

Instron Tear Test
Lbs./ft.

Instron Breaking Strength
Lbs./in.

Opacity

Flammability

Care & Handling

Testing & Certifications

Color & Embossing

Solar Control
(12 oz 4-ply)

Fabrication

Application

Ask us about our other fabric lines which include: Cotela-TFR, the Apagón Collection, the Vision Collection, and the Commercial Collection

info@indianacoatedfabrics.com

the Standard Blackout

4 ply (Vinyl, Fiberglass)

60 threads per square inch

36", 54", 63", 72", 77"
(91 cm, 137 cm, 160 cm, 183 cm, 196 cm)

33 yards (33 m) on 3" cores
(Other lengths available upon request)

12 oz per square yard
(424 grams per square meter)

12.5 mil (.318 mm)

Warp: 25.87 Fill: 17.53

Warp: 100 Fill: 77

Blackout

NFPA 701 Test Method 1 - 2019 Edition
Also available as "Ultra" (CAN-ULC-S109)

May be dusted with damp cloth. Warm water, mild detergent with gentle rubbing when scrubbing is necessary

NFPA Standard 701/2019 Test Method 1

FMVSS & CMVSS 302

California State Fire Marshal Sec. 13115 Registration FA-35801

SW 846-7000B-7420 (Pb) - Lead

ASTM D4834-03/CSA-CAN 600.008 Lead

ASTM G-21 Resistance to Fungi

the Economy Wide Shade

4 ply (Vinyl, Fiberglass)

60 threads per square inch

98", 120"
(249 cm, 305 cm)

25 yards (23 m) on 3" cores
(Other lengths available upon request)

14.5 oz per square yard
(492 grams per square meter)

15.2 mil (.386 mm)

Warp: 40.05 Fill: 21.61

Warp: 293.33 Fill: 304.62

Blackout

NFPA 701 Test Method 1 - 2019 Edition
Also available as "Ultra" (CAN-ULC-S109)

ATCC 6275 Aspergillus Niger/ATC 9645 Trichoderma Virus

ASTM E1428-9 Pink Staining

AATCC 183 - UV Blocking

AATCC 16, Option 3 - 2003 Colorfastness to Light

ASHRAE Standard 74-1988 - Fenestration

GreenGuard - Gold Certified

the Wide Shade IV

4 ply (Vinyl, Fiberglass)

68 threads per square inch

98", 120"
(249 cm, 305 cm)

25 yards (23 m) on 3" cores
(Other lengths available upon request)

17.5 oz per square yard
(606 grams per square meter)

16.9 mil (.42 mm)

Warp: 9 Fill: 10

Warp: 339 Fill: 256

Blackout

NFPA 701 Test Method 1 - 2019 Edition
Also available as "Ultra" (CAN-ULC-S109)

Color Matrix	White to Grey Tones															Neutral to Brown Tones															Colors									
	White	Cloud White	Azure White	Light Grey	Arctic Silver	Grey	Platinum Grey	Dark Grey	Mineral Dust	Sage	Pepper	Graphite	Black	Warm White	Cream	Bone	Ivory	Vanilla	Oyster	Clay	Alabaster	Palomino	Dark Sand	Light Cocoa	Buff	French Beige	Champagne	Autumn Wheat	Celadon	Lilac	Linen	Suede	Bark	Chocolate	Mocha	Wine	Ecru	Forest Green	Denim	
	105	106	48	92	47	139	49	111	113	58	18	142	10	26	37	23	51	71	57	34	103	104	84	36	26	9	32	72	101	100	134	133	17	33	189	77	38	45	35	
	X				X		X	X	X	X	X	X	X	X		X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X
	X					X		X	X	X	X	X	X	X		X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	
	X					X		X	X	X	X	X	X	X		X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	
	X					X		X	X	X	X	X	X	X		X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	
	X					X		X	X	X	X	X	X	X		X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	
	X					X		X	X	X	X	X	X	X		X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X
	X					X		X	X	X	X	X	X	X		X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X

Embossing Pattern	the Standard (36", 54", 63", 72", 77")	Wide Shade (98" & 120")
Matte	X	X
DeLux	X	X
Moire	X	X
Boucle	X	X
Cloud	X	
Pebble	X	
Windsor	X	
Medina	X	
Leather	X	
Linen Plus	X	
Topaz	X	X
Softglass	X	

Solar Heat Control Properties																
Interior Use at Zero Degree Profile Angle																
No.	Color	Ts	Rs	As	Tv	Rv	Av	Tv	Q-F	SC (Single Glass)			SC (Insulating Glass)			
										1.8" C I	1.4" C I	1.4" H A	1.2" C I	1" C I	1" H A	
11	White 4 Ply	Tr	77	23	Tr	NA	NA	NA	NA	NA	0.22	NA	NA	0.2	NA	NA
23	Bone 4 Ply	Tr	69	31	Tr	59	41	Tr	0.2	0.27	0.28	0.29	0.26	0.28	0.23	
47	Grey 4 Ply	Tr	45	55	Tr	Tr	Tr	NA	NA	0.44	0.43	0.37	NA	NA	NA	NA
49	Dark Grey 4 Ply	Tr	30	70	Tr	28	72	Tr	0.2	0.55	0.53	0.42	0.52	0.49	0.35	
10	Black 4 Ply	Tr	5	96	Tr	Tr	Tr	NA	NA	0.72	0.68	0.5	NA	NA	NA	

Cutting: Cold, Electric Rotary Sheer, Straight Knife, Crush Cut, Ultrasonic | Welding: Heat Seal, RF

Roller Shade, Panel Track, Verticals, Banner/Print Media



Indiana Coated Fabrics

www.indianacoatedfabrics.com

102 Enterprise Drive - P.O. Box 1017 - Warsaw, IN 46581