

Specifications	Fabric Line
	Construction
	Surface Texture
	Thread Count
	Available Widths
	Roll Lengths
	Weight
	Thickness
	Instron Tear Test Lbs./In.
	Instron Breaking Strength Lbs./In.
	Opacity
	Flammability
	Care & Handling
	Testing & Certifications
	Key Advantages
	Fabrication Application

## Vision Plus

3 ply (Polyester, Proprietary Coating, PCE Film)

*Front Side:* Fabric fronted woven polyester with a proprietary coating & coloring;  
*Back Side:* Laminated White Backing with optional Coloring available

126 threads per square inch  
 (49.6 per square centimeter)

98" (249 cm)

25 yards (23 m) on 3" cores

17.9 oz per square yard  
 (606.9 grams/square meter)

23 mil (.584 mm)

Warp: 3.36      Fill: 19.60

Warp: 327.04      Fill: 128.16

Blackout

NFPA 701 Test Method 1 - 2019 Edition

May be dusted with damp cloth. Warm water, mild detergent with gentle rubbing when scrubbing is necessary

ASTM G-21-15 Resistance to Fungi

Custom coloring and Front/Back Color Match available\*\*

- Resistance to direct sunlight; Will not crack, chip or yellow like PES foam backed fabrics
- Flexibility; fabric will retain its natural state
- High-end decorative look
- Durability; front and back do not flake or scratch
- Ultra stable
- Prop 65 & Massachusetts FR Approved

**Cutting:** Cold, Electric Rotary Sheer, Straight Knife, Crush Cut, Ultrasonic | **Welding:** Heat Seal, RF Roller Shade, Panel Track, Verticals

Fabric Swatches

### Colors

- White #11
- Clay #34
- Grey #47
- Dark Grey #49
- Black #10

Ask about our HPD program availability

\*\*MOQ may apply

Ask us about our other fabric lines which include: Cotela-TFR, the Iconic Blackout Collection, the Apagon Collection, Projection Screen and Artisit Media  
[info@indianacoatedfabrics.com](mailto:info@indianacoatedfabrics.com)



[www.indianacoatedfabrics.com](http://www.indianacoatedfabrics.com)

102 Enterprise Drive - P.O. Box 1017 - Warsaw, IN 46581

