




Fabric Specification Sheet

Style:	<u>Apagòn Style III</u>	
Available Width:	98" (249 cm)	
Roll Length:	30-yard standard (27 Meters)	
Shipping:	Rolls shipped on 3" (7.62 cm) ID paper core	
Construction:	3 ply (62.1% Vinyl, 31.6% Fiberglass, 6.2% Proprietary Coating) (Each vinyl is equal thickness and weight)	
Surface Texture:	Back side laminated with color coated front side	
Thread Count:	59 threads per square inch (23 per square centimeter)	
Weight:	12.8 ounces (436.7 grams/m ²)	(+ or - 2.0) (+ or - 68)
Thickness:	13.1 mil (.333 millimeters)	(+ or - 2.0) (+ or - .05)
Instron Tear Strength:	Warp 17.13 Lbs/In	Fill 11.43 Lbs/In
Instron Breaking Strength:	Warp 298.26 Lbs/In	Fill 299.72 Lbs/In
Opacity:	Blackout	
Visual check Washability:	Material may be dusted with a damp cloth. When scrubbing is necessary, warm water, mild detergents and gentle rubbing are recommended.	
Flammability:	National Fire Protection Association Standard 701-2019 Test Method 1	
Other Tests Passed:	AATCC Test Method 16-3 – Colorfastness to Light ASTM D3335 85a - Lead Testing ASTM Method G-21-15 – Resistance to Fungi UL GreenGuard Gold Certified ASTM C423 – Sound Absorption (NRC Rating 0.05 – SAA Rating 0.05) AATCC Test Method 16 – Colorfastness to Light AATCC Test Method 30-2013 – Fungal Growth (Trichoderma virens – ATCC #9645) (Aspergillus niger – ATCC #6275) ISO 22196:2011 – Antibacteria (Staphylococcus aureus – ATCC #6538)	



8/2020

MAILING ADDRESS
P.O. Box 1017
Warsaw, IN 46581

STREET ADDRESS
102 Enterprise Drive
Warsaw, IN 46580

PHONE
(574) 269-1280

FAX
(574) 269-7747

E-MAIL
Mail@indianacoatedfabrics.com

WEBSITE
www.indianacoatedfabrics.com